


8 FT. OR 16 FT.

8 CONDUCTOR FLAT CABLE



|    |                                |                                |   |
|----|--------------------------------|--------------------------------|---|
| 5  | (RED) TRANSMIT DATA TO REG.    | (RED) RECEIVE DATA FROM SCALE  | 4 |
| 6  | (BLACK) RECEIVE DATA FROM REG. | (BLACK) TRANSMIT DATA TO SCALE | 3 |
| 23 | (BLUE) GROUND                  | (BLUE) GROUND                  | 7 |
|    |                                | (BROWN) DTR                    | 8 |
|    |                                | (ORANGE) DSR                   | 2 |
|    |                                | (GREEN) RTS                    | 5 |
|    |                                | (YELLOW) CTS                   | 6 |

PINS 8 & 2 MUST BE SHORTED TOGETHER  
AND PINS 5 & 6 MUST BE SHORTED TOGETHER.  
BUT DUE TO THE FACT THAT PINS CANNOT BE  
SHORTED TOGETHER ON THE "RJ-45" CONN.  
CONNECT THE WIRES TO THE PINS AND  
SHORT THEM OUT ON THE 25 PIN CONN. SIDE.

**CAS CORPORATION (U.S.A.)**

99 MURRAY HILL PARKWAY // EAST RUTHERFORD, N.J. 07073

TEL: (201) 933-9002

FAX: (201) 933-9025

INTERFACE WITH:

**CRS IF CABLE, RS-232**

DRAWN BY:

JIM FLOOD (SERVICE DEPT.)

DATE:

3/12/97

REV.

A

PART #:

7880-PD0-4141 (8 FT.)

7880-PD1-4141 (16 FT.)

SHEET 1 OF 1